

PAT-NO: JP404004766A
DOCUMENT-IDENTIFIER: JP 04004766 A
TITLE: ULTRASONIC MOTOR
PUBN-DATE: January 9, 1992

INVENTOR-INFORMATION:

NAME
MYOGA, OSAMU
INOUE, TAKESHI

ASSIGNEE-INFORMATION:

NAME	COUNTRY
NEC CORP	N/A

APPL-NO: JP02102448
APPL-DATE: April 18, 1990

INT-CL (IPC): H02N002/00

US-CL-CURRENT: 310/333

ABSTRACT:

PURPOSE: To make the efficiency and torque of a wave motor higher by employing a ring member material having the product of density and sound velocity not less than $18.71\text{kg/m}^2\text{sec}$. and not more than $34.75\text{kg/m}^2\text{sec}$. in an ultrasonic motor using a longitudinal and torsional coupling oscillator as stator thereby matching the resonance frequencies of longitudinal and torsional oscillations to each other.

CONSTITUTION: Intermediate cylinders 16a and 16b being ring members with a support 17 between are arranged between longitudinal oscillation driving and torsional oscillation driving piezoelectric elements 10 and 11. These members

are held between a head mass 12a and rear mass 13 and firmly fastened by a nut

14. A rotor 18 is pressure-welded to the stator of said constitution by a

spring in the manner of rotating around a shaft. In this case, the ring

members are made of a material having the product of density and sound velocity

between $18.7\text{kg/m}^2\cdot\text{sec.}$ and $34.75\text{kg/m}^2\cdot\text{sec.}$

COPYRIGHT: (C)1992,JPO&Japio